

Cyrus Audio, November 2023

Warranty 2 years, Prices in CHF, VAT included, product and price changes reserved, replaces all previous price lists

Streaming Packs	Streamer + Integrated Amplifier (for details and specs see below)	
NEW: SP Classic	Classic Stream + Classic AMP (for details and specs see below)	4290
NEW: SP XR	Stream-XR + i9-XR (for specs see below)	5790
Pre / Power Packs	Preamplifier + Poweramplifier (for details and specs see below)	
NEW: PPP Classic	Classic PRE + Classic POWER (for details and specs see below)	4990
NEW: PPP XR	Pre-XR + Power-XR (for specs see below)	6990
Turntable	Available in black only	
NEW: TTP	Turntable - solid single billet aluminium damped chassis - high precision self-lubricating bearing - solid single billet aluminium platter - adjustable / replaceable feet - Rega RB330 lightweight tonearm with optimised resonance control and near frictionless movement - integrated DC synchronous motor - custom-designed digital control circuit for excellent speed stability - electronic speed control for 331/3 and 45 RPM - PSX-R2 upgradable for highest possible speed stability - without cartridge - size (W x D x H) 438 x 395 x 75mm - weight 24kg	4290
NEW: TTP cover	Optional dust cover for TTP turntable	390
XR series	Available in phantom black only	
Source components		
NEW: Stream-XR	High-Performance Streaming Music Player - 32bit 2nd Gen QXR DAC topology - BluOs operating system - Amazon Music, Deezer, Idagio, Napster, Qobuz, Spotify, Tidal streaming services - Tunein internet radio - ROON ready - AirPlay2 - supported formats: FLAC, ALAC, WAV, AIFF, MQA, MPEG-4_SLS, MP3, AAC, WMA, WMA-L, OGG - volume control - PSU-XR upgradable / connection - 1x Coax RCA digital in, 1x TOS digital in (24/192) - 1x Coax RCA digital out, 1x TOS digital out (24/192) - 1x RCA analog out	2990

Source components continued

CDi-XR	<p>CD-Player</p> <ul style="list-style-type: none"> - Servo Evolution technology for cleaner digital data stream and lowest possible noise induced into analogue output stages - 32bit 2nd Gen QXR DAC - independent and multiregulated powersupplies for digital and analog section using 'counter-current' methodologies to minimise noise pickup - PSU-XR upgradable / connection - user upgradable firmware - 1x SPDIF RCA out, 1x TOS out, 2x RCA analog out, - 1x usb mini firmware upgrade port, includes iR14 remote control 	2590
CDt-XR	<p>CD-Transport</p> <ul style="list-style-type: none"> - Servo Evolution technology for cleaner digital data stream lowest possible noise induced into analogue output stages - 32bit 2nd Gen QXR DAC - digital signal re-clocking just before output ensuring purity of outbound digital - independent and multiregulated powersupplies for digital and analog section using 'counter-current' methodologies to minimise noise pickup - PSU-XR upgradable / connection - user upgradable firmware - 1x SPDIF RCA out, 1x TOS out, - 1x usb mini firmware upgrade port, includes iR14 remote control 	2890

Amplifying components

i9-XR	<p>Integrated amplifier WITH DAC and PHONO MM input</p> <ul style="list-style-type: none"> - preamp section using Pre-XR technology featuring a new high-performance gain stage - 32bit 2nd Gen QXR dac topology with seven digital filter alignment options - over specified power supply - input sensitivity and naming for each input variable - 2x 91w @ 6ohms - PSU-XR upgradable / connection - 1x RCA phono MM in, 4x RCA line in - 2x Coax RCA in, 2x TOS in (24/192), 1x async USB in (32/384, DSD512/DOP128) - 1x RCA analog pre out, 1x RCA fixed analog out - 1x 3.5mm headphone analog output, 2x BFA (hollow) banana speaker out L/R - 1x usb mini firmware upgrade port, includes iR14 remote control 	3890
Pre-XR	<p>Preamplifier WITH DAC and PHONO MM input</p> <ul style="list-style-type: none"> - New Pre-XR technology featuring a new high-performance gain stage - 32bit 2nd Gen QXR dac topology with seven digital filter alignment options - over specified power supply - input sensitivity and naming for each input variable - PSU-XR upgradable / connection - 1x RCA phono MM in, 4x RCA line in - 2x Coax RCA in, 2x TOS in (24/192), 1x async USB in (32/384, DSD512/DOP128) - 1x RCA, 1x XLR analog pre out, 1x RCA fixed analog out - 1x 3.5mm headphone analog output - 1x usb mini firmware upgrade port, includes iR14 remote control 	4890
NEW: Power-XR	<p>Stereo power amplifier</p> <ul style="list-style-type: none"> - wide bandwidth design for flat frequency response and minimal phase shift through audio band - generous, over-specified power supply - 2x 110w @ 6ohms - > 100kHz frequency response (-3dB) - <0.002% THD+N (6ohms, 1kHz, 2/3 power) - PSU-XR upgradable / connection - 1x RCA, 1x XLR, 1x RCA chain out - 1x banana speaker output L/R - 12V trigger input - 1x usb mini firmware upgrade port 	3390
NEW: PSU-XR	<p>High performance intelligent external power supply</p> <ul style="list-style-type: none"> - houses five independent power supplies - minimises electrical noise with help of fifteen separate transformer windings, ground isolated regulation circuitry, separate output power and ground returns in the connecting cable - intelligently automatically adjusts to connected XR component meeting respective requirements - upgrades the following products: CDi-XR, CDt-XR, i9-XR, Stream-XR, Pre-XR 	2690

CLASSIC series Available in black only

Source components

NEW: Classic STREAM	High-Performance Streaming Music Player - 32bit 2nd Gen QXR DAC topology - BluOs operating system - Amazon Music, Deezer, Idagio, Napster, Qobuz, Spotify, Tidal streaming services - Tunein internet radio - ROON ready - AirPlay2 - supported formats: FLAC, ALAC, WAV, AIFF, MQA, MPEG-4_SLS, MP3, AAC, WMA, WMA-L, OGG - volume control - PSX-R2 upgradable / connection - 1x Coax RCA digital out, 1x TOS digital out (24/192) - 1x RCA analog out	2390
CDi	CD-Player - Cyrus Servo mechanism - 32bit DAC with upsampling - independent and multiregulated powersupplies for digital and analog section - PSX-R2 upgradable / connection - 1x SPDIF RCA out, 1x TOS out, 2x RCA analog out - includes iR14 remote control	1790
CDt	CD-Transport - Cyrus Servo mechanism - isolated and multiregulated powersupply - 1x SPDIF RCA out, 1x TOS out - includes iR14 remote control	1390

Amplifying components

Phono Signature	Signature phono preamplifier - switchable inputs for 4 turntables, each input individually configurable for MM or MC cartridges - gain, resistance and capacitance individually configurable for each input - settings are saved into memory, settings and memory function remote controllable - passive RIAA filtering with very high performance metallized polyester capacitors - Warp filter to reduce bass unit excursion on warped records - PSX-R2 upgradable / connection - 4x RCA line input, 4x ground connector - 1x RCA, 1x XLR analog out - includes iR14 remote control	2190
NEW: Classic AMP	Integrated amplifier WITH DAC and PHONO MM input - wide bandwidth design for flat frequency response and minimal phase shift through audio band; preamp section with new precision gain control for volume and analogue input selection via relays - bespoke 32bit QXR dac card - input sensitivity and naming for each input variable - 2x 91w @ 6ohms - PSX-R upgradable / connection - 1x RCA phono MM in, 4x RCA line in - 2x Coax RCA in, 2x TOS in (24/192) - 1x RCA analog pre out, 1x RCA fixed analog out - 1x 3.5mm headphone analog output, 1x banana speaker out L/R - 1x usb mini firmware upgrade port, includes iR14 remote control	2390
NEW: Classic PRE	Preamplifier WITH DAC and PHONO MM input - wide bandwidth design for flat frequency response and minimal phase shift through audio band; new precision gain control for volume and analogue input selection via relays - bespoke 32bit QXR dac card - input sensitivity and naming for each input variable - PSX-R upgradable / connection - 1x RCA phono MM in, 4x RCA line in - 2x Coax RCA in, 2x TOS in (24/192) - 1x RCA, 1x XLR analog pre out, 1x RCA fixed analog out - 1x 3.5mm headphone analog output - 1x usb mini firmware upgrade port, includes iR14 remote control	2990

CLASSIC series continued

X Power	Bridgeable stereo power amplifier - protection system - auto turn on with incoming signal - 2x 100w @ 6ohms, bridgeable to 1x 181x @ 6ohms - PSX-R2 upgradable / connection - 1x RCA line in, 1x RCA chain out - 2x BFA (hollow) banana speaker output L/R	1690
NEW: Classic POWER	Stereo power amplifier - wide bandwidth design for flat frequency response and minimal phase shift through audio band - generous, over-specified power supply - 2x 110w @ 6ohms - > 48kHz frequency response (-3dB) - <0.002% THD+N (6ohms, 1kHz, 2/3 power) - PSX-R2 upgradable / connection - 1x RCA, 1x XLR, 1x RCA chain out - 1x banana speaker output L/R - 12V trigger input - 1x usb mini firmware upgrade port	2590
PSX-R2	Highly enhanced high performance external power supply - fully regulated 300W DC, connectivity adjusting automatically to connected Cyrus component - upgrades the following products: CDi, Classic STREAM, Classic AMP, Classic PRE, X Power	1190
Upgrades / Accessories		
QXR DAC card	Upsampling and oversampling 32/768 DAC card upgrade	690
iR14	Remote control	79
RACK		
Hark III	System rack including 4 fully adjustable shelves (one unit per shelf); can take up to 8 shelves; Cyruthane Isopads; cables hidden in column	890
Hark III 2 shelves pack	2 additional shelves for Hark III	149

ONE SERIES	Available in black only	
One	<p>Integrated amplifier WITH Bluetooth aptX and phono MM input, app controllable</p> <ul style="list-style-type: none"> - Bluetooth aptX connectivity, allows streaming in CD quality - high quality phono MM input - Speaker Impedance Detection (SID) automatic impedance match to connected speaker - class AB headphone amplifier - 2x 100w @ 8ohms <p>Connections: Bluetooth aptx, 4x RCA line input, 1x RCA variable analog output (pre out), 1x 6.3mm headphone analog output, 2x banana speaker output L/R</p>	990
One Cast	<p>Integrated amplifier WITH Google Chromecast, Apple Airplay2, Bluetooth aptX-HD, digital inputs and phono MM input</p> <ul style="list-style-type: none"> - Chromecast, Apple Airplay2, and Bluetooth aptX-HD connectivity - Voice controllable - Hires digital inputs including async USB - high quality phono MM input - Speaker Impedance Detection (SID) automatic impedance match to connected speaker - class AB headphONE amplifier - 2x 100w @ 8ohms <p>Connections: Chromecast, Apple Airplay2, Bluetooth, 1x USB B, 1x TOS, 1x Coax digital in, 1x RCA line in, 1x RCA pre out, 1x 6.3mm headphone analog output, 2x banana speaker output L/R</p>	1590
One Linear	<p>2-way bookshelf speaker; reflex enclosure (pair)</p> <ul style="list-style-type: none"> - high gloss finish black or white - nominal impedance 8Ω, sensitivity (2.83V@1m) 86dB, recommended amplifier power 20-120W - frequency response (±3dB) 50Hz-24kHz, crossover frequency 2.1kHz, cabinet volume 11l - bass driver 5" (125mm) woven kevlar cone, treble driver 1" (25mm) soft dome - dimensions (H x W x D) 305 x 200 x 295 mm, net weight 14 kg (per pair) 	590
One Bundle	<p>One Bundle</p> <ul style="list-style-type: none"> - One integrated amplifier and One Linear, 2-way bookshelf speaker; reflex enclosure (pair) 	1390
One Cast Bundle	<p>One Cast Bundle</p> <ul style="list-style-type: none"> - One Cast integrated amplifier and One Linear, 2-way bookshelf speaker; reflex enclosure (pair) 	1990