

Murasakino, November 2023

Warranty 1 year, Prices in CHF, VAT included, product and price changes reserved, replaces all previous price lists

Stereo Cartridge

Sumile	8990
Retip Sumile	5490

Technical Data	Frequency response: 10-50'000Hz Output voltage: 0.35mV @ 1kHz Internal impedance: 1.2 Ohm Tracking force: 1.9-2.1g Cantilever material: Boron Diamond cut: Semi Line Contact Weight: 14.5g
----------------	--



Mono Cartridge

Sumile Mono	8990
Retip Sumile Mono	5490

Technical Data	Frequency response: 10-30'000Hz Output voltage: 0.4mV @ 1kHz Internal impedance: 1.5 Ohm Tracking force: 2.7-3.3g Cantilever material: Duralumin (A2017) Diamond cut: Semi Line Contact Weight: 14.5g
----------------	---



Step-Up Transformers

Murasakino strongly recommends using an MC (step-up) transformer rather than a MC phono preamplifier for electrical advantages (no noise induced by amplification; MC cartridge signals are received not as voltages but as electrical power). However, the most important reason is the sound quality: Good,

Nobala	8990
--------	------

Technical Data	Frequency response: 10-70'000Hz Boost ratio: 26db Cartridge internal impedance: 5 Ohm or less Dimensions: 166mm (W) x 95mm (H) x 155mm (D) Weight: 2.6kg
----------------	--



MT-510	4490
--------	------

Technical Data	Frequency response: 10-58'000Hz Boost ratio: 25db Cartridge internal impedance: 12 Ohm or less Dimensions: 160mm (W) x 79mm (H) x 110mm (D) Weight: 1.8kg
----------------	---

